

SJ-HS

This Stainless Steel Weighing Pan is extremely practical for all kinds of hygienic applications



SJ-1000HS SJ-2000HS SJ-5000HS SJ-12KHS



A&D ...Clearly a Better Value
A&D Company, Limited
<http://www.aandd.jp>

Food service, Stores, Post offices, Industries, Factories, Schools, Laboratories, Warehouses, Offices, Home use and a wide range of other diverse weighing applications are possible.

■ Stainless steel weighing pan

■ High resolution

(SJ-5000HS:1/2500, SJ-12KHS:1/2400, SJ-1000HS/2000HS: 1/2000)

■ Fast stability time – Less than 1 second



■ Large wide LCD display (25mm height)

■ Durable body

■ Large weighing pan 230mm x 190mm



■ Full digital calibration function

■ Multiple weighing units – g, lb, oz and lb-oz



■ Battery operation with 4 x D size dry batteries

■ Simple and easy to change the batteries

■ Optional AC adapter



■ Automatic power OFF function

■ Spirit level and adjustable feet for accurate weighing

■ Status indication function – Battery, Stable, Zero and Net

SJ-HS Specifications

	SJ-1000HS	SJ-2000HS	SJ-5000HS	SJ-12KHS
Capacity x Resolution	g	1000g x 0.5g	2000g x 1g	5000g x 2g
	lb	2.2lb x 0.001lb	4.4lb x 0.002lb	11lb x 0.005lb
	oz	35oz x 0.02oz	70oz x 0.05oz	176oz x 0.1oz
	lb-oz	2.2lb x 0.1 oz	4.4lb x 0.1 oz	11lb x 0.1oz
Linearity	±1g	±2g	±5g	±10g
Repeatability (S.D.)	1g	2g	5g	10g
Span drift	±0.015% / °C TYP (5°C~35°C/ 41°F~95°F)			
Display	Liquid Crystal Display , 25mm / 0.98 inches			
Operating temperature	-10°C~40°C / 14°F~104°F, less than 85% RH (No condensation)			
Display update	Approx. 10 times per second			
Power	4 x R20P / LR20 / "D" size batteries or AC adapter			
Battery life	Approx. 800 hours with alkaline cells at 20°C / 68°F			
Pan size	230 (W) x 190 (D) mm / 9.05 (W) x 7.48 (D) inches			
Dimensions	265 (W) x 250 (D) x 103 (H) mm / 10.4 (W) x 9.8 (D) x 4.1 (H) inches			
Weight	Approx. 2.1kg / 4.6lb			
Calibration mass	1000g	2000g	5000g	10kg

Specifications subject to change for improvement without notice

External Dimensions (mm / inches)



Local Supplier:

Perth Scale & Slicer Service

Unit 1, 195 Bannister Road Canning Vale

PH: 08 9256 2544

Web: www.perthscale.com.au

Accessories

AX-TB164B	AC adapter	AC 230V "C" type plug
AX-TB173A	AC adapter	AC 230V "BF" plug
AX-TB196	AC adapter	AC 100 "A" type plug
AX-TB202	AC adapter	AC 120 "A" type plug



...Clearly a Better Value

A&D Company, Limited

3-23-14 Higashi-Ikebukuro, Toshima-ku, Tokyo 170-0013 JAPAN
Telephone: [81](3) 5391-6132 Fax: [81](3) 5391-6148
<http://www.aandd.jp>

A&D ENGINEERING, INC.

1555 McCandless Drive, Milpitas, CA, 95035 U.S.A.
Telephone: [1](408) 263-5333 Fax: [1](408) 263-0119

A&D MERCURY PTY. LTD.

32 Dew Street, Thebarton, South Australia 5031 AUSTRALIA
Telephone: [61](8) 8301-8100 Fax: [61](8) 8352-7409

A&D INSTRUMENTS LTD.

Unit 24/26 Blacklands Way Abingdon Business Park,
Abingdon, Oxon OX14 1DY United Kingdom
Telephone: [44](1235) 550420 Fax: [44](1235) 550485

<German Sales Office>

Große Straße 13 b 22926 Ahrensburg GERMANY
Telephone: [49](0) 4102 459230 Fax: [49](0) 4102 459231

A&D KOREA Limited

Manhattan Bldg. 8F, 36-2 Yoido-dong, Youngdeungpo-gu, Seoul, KOREA
Telephone: [82](2) 780-4101 Fax: [82](2) 782-4280

A&D RUS CO. LTD.

Korp. 134A, D.29, UL. Vereiskaya, Moscow, 121357
RUSSIAN FEDERATION
Telephone: [7] (495) 727-4455 Fax: [7] (495) 727-4456