

Mass Comparators

MC

series

MC-1000

1100 g × 0.0001 g

MC-6100

6100 g × 0.001 g

MC-10K

10.1 kg × 0.001 g

MC-30K

31 kg × 0.01 g

MC-100KS

101 kg × 0.1 g



MC-10K



MC-6100



MC-100KS

**New model
added!**



AND
A&D Weighing

www.andweighing.com.au

Revealed—Here Are What A&D Use To Manage Their Masses!

Are you finding it difficult to find high performance, quality mass comparators that meet your budget? Discover how A&D, an ISO17025 accredited calibration laboratory as well as being a weighing equipment manufacturer, has the solution for you!

1. Enhanced stabilizing filter

High resolution balances like the MC series can respond to even the slightest environmental disturbances. For smooth and accurate mass comparison, the MC series is equipped with a special stabilizing function that copes with the effect of drafts or vibrations.

2. Simplified calibration of the balance


Using the internal mass, you can ensure the balance accuracy with one key press when changes to the environment (such as temperature or location) take place. The internal mass value can be corrected as necessary.

3. Various options to minimize possible measurement errors

Even under a perfectly controlled weighing environment, there still remain errors that can arise from operation. The following tools are effective in managing such errors:

Auto-centering pan (available for MC-1000/6100/10K/30K)

Corrects eccentric loading automatically by bringing the mass to the center.



MC Series
with auto-centering pans




Remote controller (AD-8922A)

Enables operations without directly touching and consequently shaking the balance.



Static eliminator (AD-1683)

Instantly neutralizes charged objects such as the operator's clothes to ensure stable weighing.



Recommended Measurement Ranges

Model	BM-20					BM-252				BM-500				MC-1000				MC-6100				MC-10K				MC-30K				MC-100KS		
	Class	E2	F1	F2	M1	M2	F1	F2	M1	M2	F1	F2	M1	M2	F1	F2	M1	M2	F1	F2	M1	M2	F1	F2	M1	M2	M1	M2				
Nominal value	1 mg																												1 mg			
	2mg																												2mg			
	5mg																												5mg			
	10 mg																												10 mg			
	20mg																												20mg			
	50 mg																												50 mg			
	100 mg																												100 mg			
	200 mg																												200 mg			
	500 mg																												500 mg			
	1 g																												1 g			
	2 g																												2 g			
	5 g																												5 g			
	10g																												10g			
	20 g																												20 g			
	50 g																												50 g			
	100 g																												100 g			
	200 g																												200 g			
	500 g																												500 g			
	1 kg																												1 kg			
	2kg																												2 kg			
	5kg																												5 kg			
	10 kg																												10 kg			
	20kg																												20 kg			
	50 kg																												50 kg			
	100 kg																												100 kg			

* Please refer to the BM series of micro analytical balances for the BM-20, BM-252 and BM-500.

Wait, there is more! If you are in the industrial sector, how about using the MC series as

Precision Balances With Extended Resolution

The MC series displays the weighing results with an extra decimal place not normally found in balances of the same capacity. Such extended resolution enables measurements of minute weight changes with heavy objects or containers. Example applications include:

Management of Liquids

- Resist inks on flat panels (glass)
- Coating materials on silicon wafers
- Moisture contents of catalysts
- Solder pastes and sealing materials on electronic parts
- Resins used for LED lenses
- Surface materials on optical lenses
- Grease in miniature bearings for hard disks

Management of Powders

- Medicines in pharmaceutical manufacturing – from full flow to minute flow
- Discharges (losses in weight) from feeders
- Wear volumes of metallic materials
- Cutting dust (contaminants) left on mechanical parts
- Particles caught by filters

Management of Gases

- Fill ration of hydrogen gas
- Gasified components

Production Line Weighing

- As precision check-weighing sensors with wider ranges



(Optional for MC-100KS)



Software



MC-10K/30K/100KS



IP65

Optional



MC-1000/6100

Specifications

New!

Models	MC-1000	MC-6100	MC-10K	MC-30K	MC-100KS
Weighing capacity	1100 g	6100 g	10.1 kg	31 kg	101 kg
Minimum weighing value	0.0001 g	0.001 g		0.01 g	0.1 g
Repeatability (standard deviation) ^{* 1}	0.0005 g (for 1 kg) 0.0004 g (for 500 g)	0.004 g (for 5 kg) 0.0015 g (for 2 kg)	0.005 g (for 10 kg) 0.004 g (for 5 kg)	0.015 g (for 20 kg)	0.2 g (for 100 kg) 0.1 g (for 60 kg)
Linearity	±0.003 g	±0.03 g		±0.2 g	±2 g
Sensitivity drift (10 to 30°C / 50 to 86°F)	±2 ppm / °C			±3 ppm / °C	±6 ppm / °C
Accuracy immediately after internal calibration ^{* 2}	±0.010 g	±0.15 g		±1.5 g	±10.0 g
Operating environment	5°C to 40°C (41 °F to 104 °F), 85%RH or less (no condensation)				
Display refresh rate	5 times/second or 10 times/second				
Display mode ^{* 3}	Gram, kilogram (for MC-100KS only), ounce, pound, pound-ounce, troy ounce, metric carat, momme, pennyweight, grain, counting mode, percent mode, density mode, and a user-programmable unit				
Standard interface	RS-232C				
Weighing pan size	128 x 128 mm	165 x 165 mm	270 x 210 mm		386 x 346 mm
External dimensions	210 (W) x 317 (D) x 86 (H) mm		300 (W) x 355 (D) x 111 (H) mm		Display unit: 260 (W) x 164 (D) x 202 (H) mm Platform: 346 (W) x 443 (D) x 130 (H) mm Cable length: 3 m
Net weight	Approx. 4.6 kg	Approx. 5.1 kg	Approx. 9.3 kg		Approx. 18 kg
Power consumption	Approx. 11 VA (supplied to the AC adapter)				Approx. 15 VA (supplied to the AC adapter)

* 1 Repeatability when the auto-centering pan or an automatic weight loader is used under good environmental conditions.

* 2 Accuracy immediately after internal calibration performed under good environmental conditions. The values are for the weighing capacities.

* 3 Either tael (Singapore/HK jewelry/Taiwan) or tola can be added upon request.

Options

For MC-1000/6100

- GX-02** *4 Quick USB interface with cable
GX-04 *4 *5 Comparator output with a buzzer/RS-232C/Current loop output
GX-06 *4 *5 Analog output/Current loop output
GX-12 Animal weighing pan
GX-13 Density determination kit (for MC-1000 only)

* 4 Only one of GX-02, GX-04, GX-06 or the standard RS-232C interface can be used.

* 5 Factory-installed options

For MC-10K/30K

- GX-04K** *6 Comparator output with a buzzer/RS-232C/Current loop output
GX-06K *6 Analog output/Current loop output
GX-07K Waterproof RS-232C cable (25P-9P, 5 m)
GXX-012 Animal weighing pan
GXX-015 Carrying case

* 6 Only one of GX-04K, GX-06K or the standard RS-232C can be used.
The MC-10K/30K are not IP65 compliant with these options.

For MC-100KS

- GP-04** *7 Comparator output with a buzzer/RS-232C/Current loop output
GP-06 *7 Analog output/Current loop output
GP-07 *8 5-meter extension cable
GP-12GP-21GP-22 Animal weighing pan
Underhook
AD-8121B printer support

* 7 Only one of GP-04, GP-06 or the standard RS-232C can be used.

* 8 Factory-installed option

Accessories

- AD-1602-E2** *9 Calibration masses, OIML class E2
AD-1602-F1 *9 Calibration masses, OIML class F1
AD-1682 Rechargeable battery unit
AD-1683 Static eliminator
AD-1684 Electrostatic fieldmeter
AD-1687 Weighing environment logger
AD-1688 Weighing data logger
AD-1689 Tweezers for calibration mass
AD-1691 Weighing environment analyzer
AD-8121B Compact printer
AD-8526 Serial/Ethernet converter
AD-8527 Quick USB adapter
AD-8920A Remote display
AD-8922A Remote controller
AX-MC1000PAN Auto-centering pan (MC-1000)
AX-MC6100PAN Auto-centering pan (MC-6100)
AX-MC10K/30KPAN Auto-centering pan (MC-10K/30K)
AX-SW128 Foot switch
AX-USB-25P Serial/USB converter

* 9 Selectable from 50 g to 20 kg.



Auto-centering pan



AD-1602

AND
A&D Australasia

ACN 26 007 556 809

Head Office
32 Dew Street
THEBARTON South Australia 5031
Telephone (08) 8301 8100
Facsimile (08) 8352 7409

Victorian Office
39 Bakehouse Road
KENSINGTON Victoria 3031
Telephone (03) 9371 1555
Facsimile (03) 9372 1193

New South Wales Office
Unit 4, 14 Abbott Road
SEVEN HILLS New South Wales 2147
Telephone (02) 9674 5466
Facsimile (02) 9674 2544

sales@andweighing.com.au
www.andweighing.com.au

Your Dealer

Perth Scale & Slicer Service

Unit 1, 195 Bannister Road
Canning Vale WA 6155
PH: 08 9256 2544
Web: <http://www.perthscale.com.au>