



solo per professionisti

Sirman Spa
Viale dell'Industria 9/11
35010 PIEVE DI CURTAROLO (PD), Italy
Tel./Fax. +39 049 9698666 / +39 049 9698688
email: info@sirman.com



Sirman Slicers , model Palladio 350 :

- Rounded design, no sharp edges and visibile screws.
- Chrome plated and ground slide rod.
- Lapped cast iron slide rod bushing.
- Vulcanized rubber stops on carriage.
- Removable support cover for thickness gauge plate.
- Stainless steel slice deflector with bayonet fitting.
- Stainless steel screws and fittings.
- Enclosed and sealed belt pulley.
- 49,5 mm distance between blade and motor.
- Bottom cover.
- Changeover electronic circuit 110-220-380 V single and three phase.
- Built in sharpening tool with bottom protection.
- Standard blade removal tool.
- 35° blade inclination
- Plastic knob.
- Plastic pushbuttons with IP67 protection rating.

Optional Stonehenge:

- Cast aluminum alloy with special ceramic-teflon coating treatment
- Ideal for sticky products processing
- Excellent product gliding and easy to clean
- Highly resistant to acids and sanitizing chemicals
- Removable parts are dishwasher safe
- Aluminum-gray finish colour.

Available versions:


- **Stonehenge:** table, blade cover, carriage, end weight
- **Stonehenge Plus:** base, table, knife rim guard, blade cover, carriage, end weight, sharpener housing



More space between blade and body machine



Large hopper






Palladio Stonehenge



Palladio Stonehenge Plus

Data sheet



Technical data

Model	PALLADIO 350
Ø Blade	mm 350 - inch. 14
Motor	watt 370 - Hp 0,50
Cut thickness	mm 23
Run of carriage	mm 310
Hopper	mm 305x270
A	mm 465
B	mm 340
C	mm 660
D	mm 575

E	mm 455
F	mm 710
G	mm 530
L	mm 590
X	mm 270
Y	mm 225
H	mm 275
W	mm 250
Net weight	kg 37
Shipping	mm 760x640x700
Gross weight	kg 46
HS-CODE	84385000