

Marine scale

UNI SYSTEM
SWEDEN
WEIGHING SOLUTIONS

marinescale.com



TECHNICAL SPECIFICATION

Capacities	3-150 kg	Can be verified according to	Directive 2009/23/EC
Platform size	286 x 345 mm 348 x 415 mm 500 x 600 mm	Compensation for	Gravity Motion Tilt
Powered by	230VAC 12-29VDC	Sealing	IP67
Power consumption	25mA at 230VAC 200mA at 24VDC	Stainless steel	EN 1.4301
		Warranty time	Two years

Approved for up to
18 % tilting and
motion 1 m/s²
at the same time!

The scale may be used
all over the world and
no recalibration is needed!

Optional equipment and accessories



Column mount and rubber mat



Rubber feet for secure mount of the scale



Controller with eSeaSystem



MARINE SCALE

Model						U14512	U14515	U14516
Platform size						286x345	348x415	500x600
Max	Graduation							
3 kg	1kg/1g	2kg/2g	3kg/5g			•		
10 kg	2kg/2g	5kg/5g	10kg/10g			•		
15 kg	5kg/5g	10kg/10g	15kg/20g			•		
30 kg	5kg/5g*	10kg/10g	20kg/20g	30kg/50g			•	•
70 kg	10kg/10g	20kg/20g	50kg/50g	70kg/100g			•	•
150 kg	10kg/10g*	20kg/20g	50kg/50g	100kg/100g	150kg/200g		•	•

*Not verified scales.

Other platform sizes and capacities can be provided.

Versions

230VAC (standard)	•	•	•
12-29VDC	•	•	•
Internal battery	•	•	•

Accessories

Approved (EC-certificate)	•	•	•
Column		•	•
Rubber mat	•	•	•
Feet for secure mount	•	•	•
Controller with or without printer	•	•	•



UNI SYSTEM SWEDEN
WEIGHING SOLUTIONS

Unisystem AB
Bergebyvagen 24
SE-685 34 TORSBY
Sweden

Phone +46-560-140 55
Fax +46-560 101 25
info@unisystem.se
www.unisystem.se

ISO 9001:2008
Org.nr 5561989731
VAT Reg. No.
SE556198973101