

Manual Gravity Feed Meat Slicer

GSP-H



The manual premium gravity feed slicer sets worldwide standards in terms of ergonomics, hygiene, and safety.

This manual slicer uses gravity and is easy to operate even when slicing heavy products thanks to its ergonomic, inclined carriage and the Bizerba precision. It stands out due to its wealth of variants. Individual and powerful slicer for a variety of products to be sliced in manual mode. This slicer consists of a powerful blade drive.

In addition, the GSP H can be fitted with Ceraclean® surface which is easy to clean and ensures easy feeding of products to the blade

Highlights

- The right carriage version for any application
- Drain on the slicing system and drain protection of liquids for a clean work station
- Optional hygienic Ceraclean® surface
- Optional energy and safety package allows automatic blade start/stop via slice thickness adjustment and visualization



Hygiene

Bizerba sharpeners are separate units representing no hygiene risk during sharpening. Of course, same as with all other removable parts, this sharpener can be cleaned in the dishwasher.

Sophisticated design, careful material selection and elegant solutions such as a lifting device for quick and easy cleaning by hand underneath the slicer.

Safety

The optional safety package "Illumination" shows the operator the machine operating state at a glance thus considerably reducing the risk of injury.

Technical Data

Voltage

- 120 V / 230 V

Housing materials

- anodized aluminum
- Bizerba Ceraclean® (optional)
- fiber-reinforced composite
- transparent plastics for food contact

max. outer dimensions L x W x H / L x W x H

- 725 x 587 x 596 mm / 28.6" x 23" x 23.5"
- Outer dimensions depending on machine version Required installation area might be larger than outer dimensions

Blade diameter

- 330 mm / 13.0"
- optionally 350 mm / 13.8"

Carriage inclination

- 0 - 25° towards operator
- Positioning in different heights towards center of blade depending on slicer version

Blade alignment

- 40° inclination

Max. product size

- Round: Ø 260 mm / 10.2"
- Height: 246 mm / 9.7"
- Width: 195 mm / 7.7"

Product dimensions depend on carriage version

Slice thickness adjustment

- Continuous 0 - 24 mm / 0 - 1.0"
- Fine setting 0 - 3 mm / 0 - 0.12"

Protection type

- IP 33

