

ADM-4406

Batching Console

The ADM-4406 Batching Console is factory configured and tested ready for installation and use.

The console contains everything that is required to suit most basic batching, bagging, filling, emptying, check weighing applications.

The onsite electrical installation is simple, all that is required are cable terminations for 240VAC mains power supply, Feeder and Load Cell connections.

The ADM-4406 standard features are:

- ✓ *Automatic and Manual Operator Controls*
- ✓ *Lamp Illumination for positive Operator Controls*
- ✓ *Internal Memory for Storing Setpoint Weight Targets*
- ✓ *Automatic Batch Count & Net Weight Totals*
- ✓ *Universal Flexi Comms for Report Print formatting*
- ✓ *Automatic Re-Start for Multi-Cycle Batching (Zero Band)*
- ✓ *Manufacturers Warranty for 12 Months*
- ✓ *Australian Designed & Manufactured to ISO 9000 Standards*

The ADM-4406 supplied standard allows the user the ability for future expansion. There are also several expansion options available for the ADM-4406 like, RS232 Serial Output, RS422/RS485 Serial I/O and 4-20mA Analog Output.



GENERAL SPECIFICATIONS

Display Resolutions	20000 Divisions Maximum (Permissible up to 40000)
Input Sensitivity	0.2uV / Division
Signal Range	-1mV up to 15mV
Load cell Drive	Four (4) x 350Ω Ohm Load cells
Output Contact Ratings	240VAC or 24VDC - Maximum 10A
Feeder Controls	Dual Speed, Fast and Slow Feed (Coarse & Dribble)
Console Enclosure Rating	Metal Painted Enclosure, IP56
Console Enclosure Size	400mm x 300mm x 210mm - Weight 9.5Kg